Max. Gross Weight Container Weight (Reefer Unit)  Max. Payload Cubic Capacity Floor Area Insulation Density Floor Strength	30,480 KG 2,430 (380) KG 27,670 KG 28.5 m³ 12.5 m² 40 - 55 kg/m³ 7,260 KG	67,200 LBS 5,360 (838) LBS 61,010 LBS 1010 ft <sup>3</sup> 135 ft <sup>2</sup> 2.5 - 3.4 lb/ft <sup>3</sup> 16,000 LBS	5449 Internal Length		Notes:  1. Cargo doors as standard. Some models may include a 'butchers' door, either in lieu of the cargo doors, or recessed behind. The butchers door will reduce internal length by approx. 200mm. Units with butchers doors will include integrated panic alarm systems, emergency lighting above the door, and automatic reefer cut-off switches to cease operation when the door is opened, among other features. Please contact Cleveland Containers for more info.
		Flat Floor	2x LED Lamps in Ceiling	SECTION A-A SCALE 1: 35	fer Unit
2438 External Width 2294 Cargo Door Opening  1			6058 External Length	o 2286 Internal Height	
	Note 1.		2050 Fork Pocket Centres		DESCRIPTION: 20' Refrigerated Container Standard Height Hire Specification  A3